

**Model
1200SJP
TELESCOPIC BOOM LIFTS**



MORE ECONOMIC

- Lower hydrocarbon, carbon monoxide, particulate and NOx emissions With Stage IIIB-compliant engine.

MORE PRODUCTIVE

- 40% gradeability for improved go-anywhere mobility around jobsites.

MORE ACCESS

- Dual capacity and class-leading reach in every direction.

SMART DESIGN

- Fewer buttons and switches used to position the platform and less time spent learning to use the platform controls.



Standard Features

- 0.91 m x 2.44 m low mount platform
- Side entry with drop bar mid rail
- Multiple function operation
- Full proportional drive joystick control with integral thumb steer switch
- Full proportional main boom and swing joystick control
- Variable speed dial control for telescope and platform rotate
- 2.44 m articulating jib
- JibPLUS* with 4 way axis jib including 180 degree horizontal motion
- Powered side stow on jib
- 180 degree powered platform rotator
- Platform console machine status light panel ¹
- Load sensing system
- AC cable to platform
- Gull-wing hoods
- Selectable dual platform capacity system (230kg/450kg)
- Drive-out extending axles
- 5 degree tilt alarm and indicator light
- Oscillating front axle
- Lifting/tie down lugs
- Hour meter
- Ground control selector switch with key lock
- Load sensing hydraulics
- Platform tool tray
- 12V DC auxiliary power
- Engine distress warning/shut down system ²
- Four wheel steer / two wheel steer/ crab steer
- Selectable creep speed on drive / lift and swing functions
- Four Wheel Drive
- Horn
- Hydrostatic drive transmission
- Swing-out engine tray
- Control ADE* Advanced Design Electronics System
- JLG Skyguard active system

¹ Provides indicator lights at platform control console for system distress, low fuel, 5 degree tilt light, and foot switch status.

Standard Specifications

Power Source	
• Diesel Engine - Deutz TCD2.914	55.4 kW
• Fuel Tank Capacity	117 L
Hydraulic System	
• Hydraulic System	250 L
• Auxiliary Power	12V DC
Tyres	
• Tyres	44S/50D/710 Foam Filled

² Low oil pressure and high coolant temperature alarms with shut-down enabled (disabled by analyst).

³ Available when integrated with the SkyPower* package.

⁴ Consists of six 40-watt lights, four turnable mounted lights and two platform mounted lights.

³ Includes platform mounted work lights and head & tail lights.

⁴ Includes console cover, boom wipers and cylinder bellows.

Accessories & Options

- 0.91 m x 1.83 m slide bar side entry platform
- 0.91 m x 1.83 m Self closing inward swing gate
- 13 mm air line to platform
- On-board 4,000 W generator
- SkyPower* package 7,500 watt on-board generator
- SkyWelder* package 250 amp welder in the platform ³
- SkyGlaizer* package glass and panel tray
- Nite-Bright* package ⁴
- All motion alarm
- Light package ³
- Flashing amber beacon
- Euro Plug & Socket
- Hostile environment kit ⁴
- Hydraulic oil cooler
- Spark Arrester Muffler
- Soft Touch 0.91 m x 1.83 m Platform Proximity System
- Soft Touch 0.91 m x 2.44 m Platform Proximity System
- Skyguard beacon (ILOS)
- Arctic package
- Generator hourmeter
- Synthetic Biodegradable Hydraulic Oil
- Platform worklights
- Head & Tail Lights
- Special paint colour
- 44S/65-24 Solid Tyres



Model 1200SJP TELESCOPIC BOOM LIFTS

Performance

- Working Height 38.73 m
- Working Outreach 23.51 m
- Swing (Continuous) 360°
- Platform Capacity
 - Restricted 450 kg
 - Unrestricted 230 kg
- Platform Rotator (Hydraulic) 180°
- Jib – Overall Length 2.44 m
- Jib – Range of articulation 130° Vertical (+75°-55°)
- JibPLUS* – Range of Articulation 180° Horizontal
 - A. Platform Size 0.91 m x 2.44 m
 - B^o. Overall Width (Axles Retracted) 2.49 m
 - B^e. Overall Width (Axles Extended) 3.81 m
 - C. Tailswing (working condition) 1.68 m
 - D. Stowed Height 3.05 m
 - E^o. Stowed Length 13.67 m
 - E^e. Transport length 10.64 m
 - F. Wheelbase 3.81 m
 - G. Ground Clearance 0.30 m
- Machine weight ¹⁾ 18,500 kg
- Maximum Ground Bearing Pressure ²⁾ 7.03 kg/cm²
- Drive Speed 5.2 km/h
- Gradeability 45%
- Axle Oscillation 0.30 m
- Turning Radius – Inside (Axles Retracted) 4.39 m
- Turning Radius – Outside (Axles Retracted) 6.86 m


¹⁾ Certain options or country standards may increase weight and/or dimensions.

²⁾ With Standard tires



2

Reach Diagram



Dimensions

